

Product data sheet

Yamaïchi


Standard wall mounted socket - front mounting




YCP-BWA15ACX-E8FSEEX-000X

YCP-BWA15ACX-E8FSEEX-000X

<https://ac-solutions-2024.digitaledoeners.be/nl/product/ycpbwa15acxe8fseex000x>



Dimensions [mm]
D1= 18.0 L1= 20.7 W1= 13.5
L2= 18.2 W2= 17.0
L3= 11.4
L4= 2.0 M1= M15x1.0
L7= 2.5



Specificaties

General Characteristics

Pin count	8 Pins Ethernet CAT6A
Size	Size 15
Housing variant	Standard
Insulator Variant	Standard
IP Grade (to contact)	IP50
IP Grade (to housing)	IP50
Mating cycles	5000 Times
Min. operating temperature	-40 °C
Max. operating temperature	+120 °C
Short Term Max. Temp	+260 °C
Vibration [Hz]	20 [10 Hz - 2000 Hz]
Shock resistance	50 [6 ms]
Salt Spray Corrosion	>144 Hours
Shielding (10 MHz)	>75 Db
Shielding (1 GHz)	>55 Db
Contact Diameter	0.7 mm

Product data sheet

Yamaïchi

Standard wall mounted socket - front mounting



Terminal cross section	Max AWG 22 / 0,34 mm²
Contact Type	Female: Solder Contacts
RoHS	2011/65/EU (2015/863/EU)

Electrical Parameters

Current rating per contact	7 A
Test Voltage Contact-Contact RMS	0.5 kV
Test Voltage Contact-Shell RMS	1.3 kV
Contact Resistance	6,5 ?

Material

Connector type digit	WA
Housing Material	Brass
Housing surface	Chrome
Contact Material and Surface	CuZn38Pb2 / min 0.75µm Au
Insulator Material	PEEK (UL)